

SEPREX

Application Guide

CONTAMINANTS	CONCENTRATION	TEMPERATURE
Adhesives	10% - 20%	71°C - 82°C
Asphaltenes	10% - 20%	71°C - 82°C
Castor Oils	10% - 20%	71°C - 82°C
Carbon Black	10% - 20%	71°C - 82°C
Coconut Oils	10% - 20%	71°C - 82°C
Cottonseed Oils	10% - 20%	71°C - 82°C
Creosote	10% - 20%	71°C - 82°C
Epoxies	10% - 20%	71°C - 82°C
#6 Fuel (Bunker C)	10% - 20%	71°C - 82°C
Heavy Lubricating Oils	10% - 20%	71°C - 82°C
Linseed Oil	10% - 20%	71°C - 82°C
Lube Oil Additives	10% - 20%	71°C - 82°C
Palm Oils	10% - 20%	71°C - 82°C
Paraffins	10% - 20%	71°C - 82°C
Pitch	10% - 20%	71°C - 82°C
Plasticizers	10% - 20%	71°C - 82°C
Resins	10% - 20%	71°C - 82°C
Soybean Oils	10% - 20%	71°C - 82°C
Tar	10% - 20%	71°C - 82°C
Tung Oils	10% - 20%	71°C - 82°C
Waxes	10% - 20%	71°C - 82°C

Notes:

1. For many applications and contaminants, ambient temperature (21°C) will suffice; however, higher temperatures increase chemical activity.
2. For application temperatures greater than 60°C, use closed-loop systems for cleaning.
3. Application duration and chemical concentration, temperature, and pressure affect performance; therefore, when evaluating a treatment, if one of these conditions is not optimal, compensate by adjusting the other application conditions.